

```
package xmlfile;

import java.io.*;
import java.util.ArrayList;
import java.util.*;

/**
 * <p>Title: XML modelling of cogwheel phase cycling MQMAS sequence</p>
 *
 * <p>Description: The resulting XML document, called mqmas.xml, models
 * the three-pulse MQMAS sequence applied to a half-integer spin system.
 * pAB is the maximum value for the coherence order between pulses A and B.
 * pBC is the maximum value for the coherence order between pulses B and C.
 * The number of steps for the cogwheel phase cycling is N.
 * The winding number (windingA or wA) of pulse A must be different of zero.
 * Those of pulses B (windingB or wB) and C (windingC or wC) are constants.
 * </p>
 *
 * <p>Copyright: Copyright (c) 2007</p>
 *
 * <p>Company: pascal-man.com</p>
 *
 * @author not attributable
 * @version 1.0
 */

public class XmlDataCogwheelWA {

    private ArrayList notes;

    public XmlDataCogwheelWA() {
        notes = new ArrayList();
    }

    /**
     * The string of addElem() contains: element
     * example1: <element>
     * example2: </element>
     * @param element String
     * @return String
     */
    public String addElem (String element) {
        return "<" + element + ">" + "\n";
    }

    /**
     * The arrayList of addElemAttriArray() contains: element, attributel,
     * attributel value, attribute2, attribute2 value, ...
     * example: <element attributel='attributel value' ...>
     * @param element ArrayList
     * @return String
     */
    public String addElemAttriArray (ArrayList element) {
        String data = new String();

        data = "<" + element.get(0);
        for (int i=1; i<element.size(); i+=2) {
            data += " " + element.get(i) + "=" + element.get(i+1) + " ";
        }
        data += ">" + "\n";
        return data;
    }
}
```

```
/**
 * The arrayList of addElemAttriEndArray() contains: element, attribute1,
 * attribute1 value, attribute2, attribute2 value, ...
 * example: <element attribute1='attribute1 value' ... />
 * @param element ArrayList
 * @return String
 */
public String addElemAttriEndArray (ArrayList element) {
    String data = new String();

    data = "<" + element.get(0);
    for (int i=1; i<element.size(); i+=2) {
        data += " " + element.get(i) + "=" + element.get(i+1) + " ";
    }
    data += " />" + "\n";
    return data;
}

/**
 * This zeroArrayList() method zeroes the ArrayList element
 * @param element ArrayList
 */
public void zeroArrayList (ArrayList element) {
    int n = element.size();
    while (n > 0) {
        element.remove(n - 1);
        n -= 1;
    }
}

/**
 *
 * @param args String[]
 */
public static void main(String[] args) {

    XmlDataCogwheelA z = new XmlDataCogwheelA();
    String elem = new String();
    int pAB = 3; //max coherence order p between 1st-pulse A and 2nd-pulse B
    int pBC = 3; //max coherence order p between 2nd-pulse B and 3rd-pulse C
    int N = 23; //winding number wA of the 1st-pulse A = N
    int windingB = 0; //winding number wB of the 2nd-pulse B
    int windingC = 1; //winding number wC of the 3rd-pulse C

    try {
        // XML file name for saving data in hard disk
        FileWriter fw = new FileWriter("mqmas.xml");

        //root of XML document
        elem = z.addElem("xml version='1.0' encoding='ISO-8859-1' ?");
        fw.write(elem);
        elem = z.addElem("<?xml-stylesheet type='text/xsl' href='mqmas.xsl' ?");
        fw.write(elem);

        //root of elements
        elem = z.addElem("mqmas");
        fw.write(elem);

        //first pulse A-----
        for (int il = -pAB; il &lt;= pAB; il++) {
            for (int jl = 1; jl &lt; N; jl++) {
                z.notes.add("A"); //A for the first pulse
                z.notes.add("p"); //p for coherence order
            }
        }
    }
}</pre
```

```
z.notes.add(String.valueOf(i1)); //pAB
z.notes.add("w"); //w for winding number
z.notes.add(String.valueOf(j1)); //wA
elem = z.addElemAttriArray(z.notes);
z.zeroArrayList(z.notes);
fw.write(elem);

//second pulse B=====
for (int i2 = -pBC; i2 <= pBC; i2++) {
    z.notes.add("B"); //B for the second pulse
    z.notes.add("p"); //p for coherence order
    z.notes.add(String.valueOf(i2)); //pBC
    z.notes.add("w"); //w for winding number
    z.notes.add(String.valueOf(windingB)); //wB
    elem = z.addElemAttriArray(z.notes);
    z.zeroArrayList(z.notes);
    fw.write(elem);

    //third pulse C, coherence order p = -1 ++++++
    z.notes.add("C"); //C for the third pulse
    z.notes.add("w"); //w for winding number
    z.notes.add(String.valueOf(windingC)); //wC
    elem = z.addElemAttriEndArray(z.notes);
    z.zeroArrayList(z.notes);
    fw.write(elem);
    //end of third pulse C+++++

    elem = z.addElem("/B");
    fw.write(elem);
}
//end of second pulse B=====

elem = z.addElem("/A");
fw.write(elem);
}
//end of first pulse A-----

elem = z.addElem("/mqmas");
fw.write(elem);
fw.close();
}
catch(IOException ex) {
    ex.printStackTrace();
}
}
```